



NOTES:

1. SEE TEXT CHAPTER 2. ROCKERIES SHALL BE DESIGNED BY A GEOTECHNICAL ENGINEER IF EMBANKMENT HEIGHT EXCEEDS 6 FT. IN A CUT SECTION OR 4 FT. IN A FILL SECTION.
2. GRAVEL BACKFILL SHALL MEET WSDOT/APWA STANDARD SPECIFICATION 9-03.12[4]
3. FLATTER SLOPE MAY BE REQUIRED IN LESS STABLE SOIL.
4. CHAIN LINK FENCE, TYPE NO. 4 OR 6 (WSDOT/APWA STANDARD), REQUIRED WHEN ROCKERY HEIGHT IS 30 INCHES OR GREATER. VINYL-COATED FENCING IN A DARK, NATURAL COLOR MAY BE USED TO IMPROVE VISUAL APPEARANCE.
5. TRAFFIC BARRIERS MAY BE REQUIRED ON ROADS WITH SPEED LIMITS OF 40 MPH OR GREATER, WHERE ROCKERY HEIGHTS EXCEED 6'. SEE CHAPTER 7 OF THE WSDOT DESIGN MANUAL.
6. IF ROCKERY IS BEHIND A ROLLED CURB OR A RURAL SHOULDER SECTION, THE ROCKERY FACE SHALL BE A MINIMUM OF 10 FT FROM EDGE OF TRAVELED WAY.

NOT TO SCALE



APPROVED BY	L. OLIVE
DATE	07/31/2008
REF STD SPEC	

DEPARTMENT OF PUBLIC WORKS
STANDARD DETAILS

ROCKERY

STANDARD DETAIL NUMBER

R-150